

6.86" RGB Series Display

Model No.: SRG0686A-4801280

RGB Interface IPS LCD Module USER MANUAL

Please click the following image to buy the sample



Business Card



WhatsApp



카카오톡



LINE (라인)



WeChat

Shenzhen Surenoo Technology Co.,Ltd.

www.surennoo.com

Skype: Surenoo365

Reference Controller Datasheet

RGB Interface LCD Module Selection Guide

CONTENTS

- 1、 GENERAL INFORMATION**
- 2、 EXTERNAL DIMENSIONS**
- 3、 ABSOLUTE MAXIMUM RATINGS**
- 4、 ELECTRICAL CHARACTERISTICS**
- 5、 BACKLIGHT CHARACTERISTICS**
- 6、 CTP CHARACTERISTICS**
- 7、 ELECTRO-OPTICAL CHARACTERISTICS**
- 8、 INTERFACE DESCRIPTION**
- 9、 INPUT TIMING**
- 10、 RELIABILITY TEST CONDITIONS**
- 11、 INSPECTION CRITERION**



1、GENERAL INFORMATION


| Item of general information | Contents | | Unit |
|-------------------------------|-------------------------------|------------------------------|---------|
| LCD Display Size (Diagonal) | 6.86 | | inch |
| Module Structure | LCD Display + CTP Touch + PCB | | - |
| LCD Display Type | TFT/TRANSMISSIVE | | - |
| LCD Display Mode | Normally Black | | - |
| Recommended Viewing Direction | ALL | | o'clock |
| Module size (W×H×T) | 189.20×76.80×8.83 | | mm |
| Active area (W×H) | 160.59×60.22 | | mm |
| Number of pixels (Resolution) | 480RGB×1280 | | pixel |
| Pixel pitch (W×H) | 0.04182×0.12546 | | mm |
| LCD Driver IC | - | | - |
| Module Interface Type | LCD | 24bit Parallel RGB interface | - |
| | CTP | I2C interface (ILI2117) | - |
| Module Input voltage | 5.0V | | V |
| Module Power consumption | - | | mW |
| Color Numbers | 16.7M | | - |
| Backlight Type | White LED | | - |



Model No.: SRG0686A-4801280

Surenno®
Display

2. EXTERNAL DIMENSIONS



3、ABSOLUTE MAXIMUM RATINGS

| Parameter of absolute maximum ratings | Symbol | Min | Max | Unit |
|---------------------------------------|--------|-----|---------------|------|
| Operating temperature | Top | -20 | 70 | °C |
| Storage temperature | Tst | -30 | 80 | °C |
| Humidity | RH | - | 90%(Max 60°C) | RH |

Note: Absolute maximum ratings means the product can withstand short-term, not more than 120 hours. If the product is a long time to withstand these conditions, the life time would be shorter.

4、ELECTRICAL CHARACTERISTICS(DC CHARACTERISTICS)


| Parameter of DC characteristics | Symbol | Min. | Typ. | Max. | Unit |
|---------------------------------|--------|---------|------|---------|------|
| PCB operating voltage | VCC5V | - | 5.0 | - | V |
| LCD I/O operating voltage | VDD | 3.0 | 3.3 | 3.6 | V |
| Input voltage 'H' level | VIH | 0.7*VDD | - | VDD | V |
| Input voltage 'L' level | VIL | VSS | - | 0.3*VDD | V |
| Output voltage 'H' level | VOH | VDD-0.4 | - | VDD | V |
| Output voltage 'L' level | VOL | VSS | - | VSS+0.4 | V |

5、BACKLIGHT CHARACTERISTICS

| Item of backlight characteristics | Symbol | Min. | Typ. | Max. | Unit | Remark |
|-----------------------------------|--------|------|-----------------|------|-------|--------|
| Forward Voltage | Vf | 8.7 | 9.3 | 9.9 | V | Note1 |
| Forward Current | If | - | 100 | - | mA | - |
| Number of LED | - | - | 3*5=15 | - | Piece | - |
| LED Connection mode | P/S | - | Serial/Parallel | - | - | - |
| Lifetime of LED | - | - | 10000 | - | hour | Note2 |

Note:

- Note1: The LED Supply Voltage is defined by the number of LED at Ta=25°C and If=100mA.
- Note2: The LED lifetime define as the estimated time to 50% degradation of initial luminous. The LED lifetime could be decreased if operating If is larger than 100mA.
- Backlight control via the BL_CTR pin or PWM signal.
- Backlight circuit:





6、CTP CHARACTERISTICS

| Item of CTP characteristics | Specification | Unit | Remark |
|-----------------------------|----------------------------|-------|--------|
| Panel Type | Glass Cover + Glass Sensor | - | - |
| Resolution | 480 × 1280 | pixel | - |
| Surface Hardness | ≥6H | - | - |
| Transparency | >82% | - | - |
| Driver IC | ILI2117 | - | - |
| Interface Type | I2C | - | - |
| Support Points | 5 | - | - |
| Sampling Rate | 20~100 | Hz | - |
| Supply voltage | 3.3 | V | - |



7、ELECTRO-OPTICAL CHARACTERISTICS

| Item of electro-optical characteristics | | Symbol | Condition | Min. | Typ. | Max. | Unit | Remark | Note |
|---|------------------------|----------------|-----------------------------------|------|-------|------|-------|--------|------|
| Response time | | Tr+Tf | $\theta=0$ $\phi=0$ Ta=25°C | - | 25 | 40 | ms | FIG 1. | 4 |
| Contrast Ratio | | CR | | - | 800 | - | - | FIG 2. | 1 |
| Luminance uniformity | | δ WHITE | | - | 80 | - | % | FIG 2. | 3 |
| Surface Luminance | | Lv | | - | 450 | - | cd/m2 | FIG 2. | 2 |
| CIE (x, y) chromaticity | White | White x | $\theta=0$ $\phi=0$ Ta=25°C | - | 0.292 | - | - | FIG 2. | 5 |
| | | White y | | - | 0.327 | - | | | |
| | Red | Red x | | - | 0.656 | - | | | |
| | | Red y | | - | 0.326 | - | | | |
| | Green | Green x | | - | 0.258 | - | | | |
| | | Green y | | - | 0.572 | - | | | |
| | Blue | Blue x | | - | 0.135 | - | | | |
| | | Blue y | | - | 0.117 | - | | | |
| Viewing angle range | $\phi=90$ (12 o'clock) | | CR \geq 10 | - | 80 | - | deg | FIG 3. | 6 |
| | $\phi=270$ (6 o'clock) | | | - | 80 | - | deg | | |
| | $\phi=0$ (3 o'clock) | | | - | 80 | - | deg | | |
| | $\phi=180$ (9 o'clock) | | | - | 80 | - | deg | | |
| NTSC ratio | | - | - | - | 60 | - | % | - | - |

Note 1. Contrast Ratio(CR) is defined mathematically by the following formula. For more information see FIG 2.:

$$\text{Contrast Ratio(CR)} = \frac{\text{Average Surface Luminance with all white pixels(P1,P2,P3,P4,P5,P6,P7,P8,P9)}}{\text{Average Surface Luminance with all black pixels(P1,P2,P3,P4,P5,P6,P7,P8,P9)}}$$

Note 2. Surface luminance is the LCD surface from the surface with all pixels displaying white. For more information see FIG 2.

Lv=Average Surface Luminance with all white pixels (P1,P2,P 3,P4, P5,P6,P7,P8,P9)

Note 3. The uniformity in surface luminance (δWHITE) is determined by measuring

luminance at each test position 1 through 9, and then dividing the maximum luminance of 9 points luminance by minimum luminance of 9 points luminance. For more information see FIG 2.

$$\delta_{\text{WHITE}} = \frac{\text{Minimum Surface Luminance with all white pixels (P1, P2, P3, P4, P5, P6, P7, P8, P9)}}{\text{Maximum Surface Luminance with all white pixels (P1, P2, P3, P4, P5, P6, P7, P8, P9)}}$$

Note 4. Response time is the time required for the display to transition from White to black(Rise Time, Tr) and from black to white(Decay Time, Tf). For additional information see FIG 1.


Note 5. CIE (x, y) chromaticity ,The x,y value is determined by screen active area position 5. For more information see FIG 2.

Note 6. Viewing angle is the angle at which the contrast ratio is greater than a specific value. For TFT module, the specific value of contrast ratio is 10.The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 3.

Note 7. For Viewing angle and response time testing, the testing data is base on Autronic-Melchers's ConoScope. Series Instruments. For contrast ratio, Surface Luminance, Luminance uniformity and CIE, the testing data is base on BM-7 photo detector.

Note 8. For TN type TFT transmissive module, Gray scale reverse occurs in the direction of panel viewing angle.

FIG.1. The definition of Response Time





8、INTERFACE DESCRIPTION

J1 Interface Description

| NO. | Symbol | I/O | DESCRIPTION |
|-------|---------|--------------|--|
| 1~2 | VCC5V | Power supply | Module Power supply(5V Typ.) |
| 3~10 | R0~R7 | I | 8bit digital Red data input(R0:LSB; R7:MSB) |
| 11 | GND | Power supply | Power ground |
| 12~19 | G0~G7 | I | 8bit digital Green data input(G0:LSB; G7:MSB) |
| 20 | GND | Power supply | Power ground |
| 21~28 | B0~B7 | I | 8bit digital Blue data input(B0:LSB; B7:MSB) |
| 29 | GND | Power supply | Power ground |
| 30 | DCLK | I | Clock signal. Latching data at the rising edge. |
| 31 | HSYNC | I | Horizontal Sync input. Negative polarity. |
| 32 | VSYNC | I | Vertical Sync input. Negative polarity. |
| 33 | DEN | I | Data input Enable. Active high to enable the data input Bus. |
| 34 | BL_CTRL | I | Backlight control pin |
| 35 | CTP_RST | I | CTP external reset signal, Low is active |
| 36 | CTP_SDA | I/O | CTP I2C data input and output |
| 37 | NC | - | No connection |
| 38 | CTP_SCL | I | CTP I2C clock input |
| 39 | CTP_INT | I | CTP External interrupt to the host |
| 40 | NC | I | No connection |




9、INPUT TIMING

| Symbol | Parameters | Min | Typ | Max | Units |
|------------|--|-----------|-----------|-----|------------|
| t_{pclk} | pclk Period | 16/18/24T | 16/18/24T | | ns |
| t_{vsys} | Vertical Sync Setup Time | 5 | | | ns |
| t_{vsh} | Vertical Sync Hold Time | 5 | | | ns |
| t_{hsys} | Horizontal Sync Setup Time | 5 | | | ns |
| t_{hsh} | Horizontal Sync Hold Time | 5 | | | ns |
| t_{hv} | Phase difference of Sync Signal Falling Edge | 0 | | W | t_{pclk} |
| t_{CKL} | pclk Low Period | 8/9/12T | 8/9/12T | | ns |
| t_{CKH} | pclk High Period | 8/9/12T | 8/9/12T | | ns |
| t_{ds} | Data Setup Time | 5 | | | ns |
| t_{dh} | Data hold Time | 5 | | | ns |

Note:

1. All timings are based on 20% to 80% of supply voltage
2. W is the number of pixel in a horizontal line
3. The pclk period depends on the bit per pixel (bpp) setting and whether the video mode is burst or non-burst mode. In burst mode, the values in the Min column should be followed. In non-burst mode, the values in the Typ column should be followed.





10、RELIABILITY TEST CONDITIONS

| No. | Test Item | Test Condition |
|-----|----------------------------|---|
| 1 | High Temperature Storage | 70°C/120 hours |
| 2 | Low Temperature Storage | -20°C/120 hours |
| 3 | High Temperature Operating | 60°C/120 hours |
| 4 | Low Temperature Operating | -10°C/120 hours |
| 5 | Temperature Cycle Storage | -10°C(30min.)~25(5min.)~60°C(30min.)×10cycles |

A、Inspection after test:

Inspection after 2~4 hours storage at room temperature, the sample shall be free from defects:

- Air bubble in the LCD;
- Sealleak;
- Non-display;
- Missing segments;
- Glass crack;
- Current is twice higher than initial value.

B、Remark:

- The test samples should be applied to only one test item.
- Sample size for each test item is 5~10pcs.
- Failure Judgment Criterion: Basic Specification, Electrical Characteristic, Mechanical Characteristic, Optical Characteristic.

11、INSPECTION CRITERION

This specification is made to be used as the standard of acceptance/rejection criteria for TFT-LCD/IPS TFT-LCD module product, and this specification is applicable only in the case that the size of module equal to or exceed than 3.5 inch.

11.1 Sample plan

Sampling plan according to GB/T2828.1-2003/ISO 2859-1: 1999 and ANSI/ASQC Z1.4-1993,normal level 2 and based on:

Major defect: AQL 0.65


Minor defect: AQL 1.5

11.2 Inspection condition

Viewing distance for cosmetic inspection is about 30cm with bare eyes, and under an environment of 20~40W light intensity, all directions for inspecting the sample should be within 45° against perpendicular line. (Normal temperature 20~25℃ and normal humidity 60 ±15%RH)

11.3 Definition of Inspection Item.

A、 Definition of inspection zone in LCD.



Zone A: character/Digit area

Zone B: viewing area except Zone A (Zone A + Zone B=minimum Viewing area)

Zone C: Outside viewing area (invisible area after assembly in customer's product)

Fig.1 Inspection zones in an LCD

Note: As a general rule, visual defects in Zone C are permissible, when it is no trouble for quality and assembly of customer's product.

B、 Definition of some visual defect

| | |
|------------|---|
| Bright dot | Because of losing all or part function, bad pixel dots appear bright and the size is more than 50% of one dot in which LCD panel is displaying under black pattern. |
| Dark dot | Dots appear dark and unchanged in size in which LCD panel is displaying under pure red, green, blue picture, or pure whiter picture. |




11.4 Major Defect

| Item No. | Items to be inspected | Inspection standard | Classification of defects |
|----------|-----------------------|---|---------------------------|
| 1 | Functional defects | 1) No display 2) Display abnormally 3) Missing vertical, horizontal segment 4) Short circuit 5) Excess power consumption 6)Backlight no lighting, flickering and abnormal lighting | major |
| 2 | Missing | Missing component | |
| 3 | Outline dimension | Overall outline dimension beyond the drawing is not allowed | |





| 4 | Polarizer defect | 5.4.1 Polarizer Position (i) Shifting in position should not exceed the glass outline dimension. (ii) Incomplete covering of the viewing area due to shifting is not allowed. | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|------------------------|---|----------------|----------------------|------------|----------------|------------|--|---|--------|-------|-----------|----------|---------|-----------|----------|------------|------------|------------|------------|---------------|-----------------|------------|--------------|---|-------|-------|---|--------|---|---|---|---|
| | | 5.4.2 Dirt on polarizer Dirt which can be wiped easily should be acceptable. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 5.4.3 Polarizer Dent & Air bubble | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <table><tr><th colspan="2" rowspan="2">Zone Size(mm)</th><th colspan="3">Acceptable Qty</th><th rowspan="3">C</th></tr><tr><th colspan="3">A+B</th></tr><tr><th colspan="2"></th><th>3.5''~7''</th><th>7~10.1''</th><th>>10.1''</th></tr><tr><td colspan="2">Φ ≤0.2</td><td>Acceptable</td><td>Acceptable</td><td>Acceptable</td><td rowspan="3">Acceptable</td></tr><tr><td colspan="2">0.2 < Φ ≤0.5</td><td>4</td><td>5</td><td>6</td></tr><tr><td colspan="2">Φ >0.5</td><td>0</td><td>0</td><td>0</td></tr></table> | | Zone Size(mm) | | Acceptable Qty | | | C | A+B | | | | | 3.5''~7'' | 7~10.1'' | >10.1'' | Φ ≤0.2 | | Acceptable | Acceptable | Acceptable | Acceptable | 0.2 < Φ ≤0.5 | | 4 | 5 | 6 | Φ >0.5 | | 0 | 0 | 0 |
| | | Zone Size(mm) | | | | Acceptable Qty | | | | C | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | A+B | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | 3.5''~7'' | 7~10.1'' | >10.1'' | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | Φ ≤0.2 | | Acceptable | Acceptable | Acceptable | Acceptable | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | 0.2 < Φ ≤0.5 | | 4 | 5 | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | Φ >0.5 | | 0 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.4.4 Polarizer scratch (i) If the polarizer scratch can be seen after cover assembling or in the operating condition, judge by the linear defect of 5.3. (ii)If the polarizer scratch can be seen only in non-operating condition or some special angle, judge by the following: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table><tr><th colspan="2" rowspan="2">Zone Size (mm)</th><th colspan="3">Acceptable Qty</th><th rowspan="3">C</th></tr><tr><th colspan="3">A+B</th></tr><tr><th>Length</th><th>Width</th><th>3.5''~7''</th><th>7~10.1''</th><th>>10.1''</th></tr><tr><td>Ignore</td><td>W≤0.05</td><td>Acceptable</td><td>Acceptable</td><td>Acceptable</td><td rowspan="3">Acceptable</td></tr><tr><td>1.0<L ≤5.0</td><td>0.05< W≤0.20</td><td>4</td><td>5</td><td>6</td></tr><tr><td>L>5.0</td><td>W>0.2</td><td>0</td><td>0</td><td>0</td></tr></table> | Zone Size (mm) | | Acceptable Qty | | | C | A+B | | | Length | Width | 3.5''~7'' | 7~10.1'' | >10.1'' | Ignore | W≤0.05 | Acceptable | Acceptable | Acceptable | Acceptable | 1.0<L ≤5.0 | 0.05< W≤0.20 | 4 | 5 | 6 | L>5.0 | W>0.2 | 0 | 0 | 0 | | | |
| Zone Size (mm) | | | Acceptable Qty | | | | C | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | A+B | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Length | Width | 3.5''~7'' | 7~10.1'' | >10.1'' | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ignore | W≤0.05 | Acceptable | Acceptable | Acceptable | Acceptable | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.0<L ≤5.0 | 0.05< W≤0.20 | 4 | 5 | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| L>5.0 | W>0.2 | 0 | 0 | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | MURA | Using 3% ND filter, it's NG if it can be seen in R,G,B picture. | Minor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | White/Black dot (MURA) | Visible under: ND3%; D≤0.15mm, Acceptable; 0.15mm<D≤0.5mm, N≤4; D>0.5mm, Not allowable. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| 6 | Glass defect | <div><div>(i) Crack</div><div>Cracks are not allowed.</div><div></div></div> | Minor | | | | | | | | |
|--|--------------|--|------------|------------|------------|------------|--------------------------------------|------|--------------------------------------|-----|-------|
| | | <div><div>(ii) TFT chips on corner</div><div></div><table><tr><th>X</th><th>Y</th><th>Z</th><th>Acceptable</th></tr><tr><td>≤3.0</td><td>≤3.0</td><td>Not more than the thickness of glass</td><td>N≤3</td></tr></table><div>Chips on the corner of terminal shall not be allowed to extend into the ITO pad or expose perimeter seal.</div></div> | X | Y | Z | Acceptable | ≤3.0 | ≤3.0 | Not more than the thickness of glass | N≤3 | Minor |
| | | X | Y | Z | Acceptable | | | | | | |
| ≤3.0 | ≤3.0 | Not more than the thickness of glass | N≤3 | | | | | | | | |
| <div><div>(iii) Usual surface crack</div><div></div><table><tr><th>X</th><th>Y</th><th>Z</th><th>Acceptable</th></tr><tr><td>≤1.5</td><td>≤1.5</td><td>Not more than the thickness of glass</td><td>N≤4</td></tr></table><div>It is only applicable to the upper glass of LCD.</div></div> | X | Y | Z | Acceptable | ≤1.5 | ≤1.5 | Not more than the thickness of glass | N≤4 | Minor | | |
| X | Y | Z | Acceptable | | | | | | | | |
| ≤1.5 | ≤1.5 | Not more than the thickness of glass | N≤4 | | | | | | | | |



11.6 Module Cosmetic Criteria

| Item No. | Items to be inspected | Inspection Standard | Classification of defects |
|----------|--------------------------------------|---|---------------------------|
| 1 | Difference in Spec. | Not allowable | Major |
| 2 | Pattern peeling | No substrate pattern peeling and floating | Major |
| 3 | Soldering defects | No soldering missing | Major |
| | | No soldering bridge | Major |
| | | No cold soldering | Minor |
| 4 | Resist flaw on PCB | Visible copper foil ($\Phi 0.5$ mm or more) on substrate pattern is not allowed | Minor |
| 5 | FPC gold finger | No dirt, breaking, oxidation lead to black | Major |
| 6 | Backlight plastic frame | No deformation, crack, breaking, backlight positioning column breaking, obvious nick. | Minor |
| 7 | Marking printing effect | No dark marking, incomplete, deformation lead to unable to judge | Minor |
| 8 | Accretion of metallic Foreign matter | No accretion of metallic foreign matter (Not exceed $\Phi 0.2$ mm) | Minor |
| 9 | Stain | No stain to spoil cosmetic badly | Minor |
| 10 | Plate discoloring | No plate fading, rusting and discoloring | Minor |
| 11 | 1. Lead parts | a. Soldering side of PCB Solder to form a 'Filet' all around the lead. Solder should not hide the lead form perfectly. | Minor |
| | | b. Components side(In case of 'Through Hole PCB') Solder to reach the Components side of PCB. | Minor |
| | 2. Flat packages | Either 'Toe'(A) or 'Seal'(B)of the lead to be covered by "Filet". Lead form to be assume over Solder.  | Minor |
| | 3. Chips | $(3/2) H \geq h \geq (1/2) H$  | Minor |
| | 4. Solder ball/Solder splash | a. The spacing between solder ball and the conductor or solder pad $h \geq 0.13$ mm. The diameter of solder ball $d \leq 0.15$ mm. | Minor |
| | | b. The quantity of solder balls or solder splashes isn't beyond 5 in 600 mm ² . | Minor |
| | | c. Solder balls/Solder splashes do not violate minimum electrical clearance. | Major |